

Timber/Combi grab

TG25HD–TG55HD

engcon[®]

TG25HD–TG55HD: For all excavators

Timber Grab, Heavy Duty Together with the tiltrotator, engcon's new TGHD timber grab is the ultimate tool for round timber handling and light sorting tasks. The grabs, which are reinforced with high strength steel wear bars with a hardness of 400 Brinell for longer service life, can be used with a large variety of hitches.

Advantages:

- High strength steel grab arms for maximum service life
- Grab tip wear bars with 400 Brinell hardness for best durability
- A non-return valve built into the hydraulic cylinder and an accumulator mounted directly onto the cylinder without hoses keeps the load safe and secure should any pressure drop occur.
- Expander bolts in joints prevent unnecessary play
- Bolt-on bracket/mounting makes it easy to switch brackets as needed.

TG25HD–TG55HD



EC-Oil™
READY



Specifications

Model	TG25HD	TG28HD	TG42HD	TG55HD
Weight: (kg)	195	360	595	1 070
Max load: (kg)	3 000	5 000	6 000	10 000
Max opening: (mm)	1 450	1 540	1 900	2 375
Width: (mm)	460	595	677	802
Grip area: (m ²)	0,25	0,28	0,42	0,55
Recommended machine weight: (tonnes) (permanent installation)	4–9	9–14	12–19	19–26
These values apply regardless of the attachment on the grab.				

TOOL SYSTEMS FOR INCREASED PROFITABILITY

engcon International Box 111, SE-833 22 Strömsund, Sweden | **Phone** +46 670 17800 | **Fax** +46 670 17828
E-mail international@engcon.com | **Web** www.engcon.com/international